AcrylPro Ceramic Tile Mastic

1
0
0

1. Product And Company Identification

Supplier

CUSTOM BUILDING PRODUCTS

13001 Seal Beach Blvd.

Seal Beach, CA 90740 UNITED STATES

Company Contact: Michael Green

Telephone Number: (562) 968-2980 Ext 115

FAX Number: (562) 903-2697 **E-Mail:** michaelg@cbpmail.net

Web Site: www.custombuildingproducts.com

Supplier Emergency Contacts & Phone Number

Infotrac: (800)-535-5053

Michael Green: (562) 968-2980 Ext 115

Manufacturer

CUSTOM BUILDING PRODUCTS

13001 Seal Beach Blvd.

Seal Beach, CA 90740 UNITED STATES

Company Contact: Michael Green

Telephone Number: (562) 968-2980 Ext 115

FAX Number: (562) 903-2697 **E-Mail:** michaelg@cbpmail.net

Web Site: www.custombuildingproducts.com

Manufacturer Emergency Contacts & Phone Number

Infotrac: (800)-535-5053

Michael Green: (562) 968-2980 Ext 115

Issue Date: 04/13/2009

Product Name: AcrylPro Ceramic Tile Mastic

CAS Number: Not Established Chemical Formula: Mixture MSDS Number: 647

Product Code: 1022.LVOC

2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight	
Acrylic Copolymer	Proprietary	10 - 20	
Calcium Carbonate	1317-65-3	55 - 65	

3. Hazards Identification

Primary Routes(s) Of Entry

Eye and Skin Contact. Inhalation. Ingestion.

Eye Hazards

Causes eye irritation.

Skin Hazards

May cause skin irritation.

Ingestion Hazards

Harmful if swallowed. May cause gastrointestinal irritation, nausea and vomiting.

Inhalation Hazards

May cause nose, throat, and lung irritation.

AcrylPro Ceramic Tile Mastic

3. Hazards Identification - Continued

Chronic/Carcinogenicity Effects

Contains chemicals that are on Californmia Prop 65 list.

Conditions Aggravated By Overexposure

May cause eye and skin irritation. May cause nose, throat and lung irritation. May cause gastronomic disturbances.

4. First Aid Measures

Eye

Gently blot or wipe any residue remaining on the face, being careful not to get it in the victim's eyes or skin. Hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

Skin

Remove excess from the skin. Wash skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Thoroughly clean before reuse. Get medical attention immediately if irritation (redness, rash, blistering) develops and persists.

Ingestion

If victim is fully conscious, give one or two cups of water or milk to drink. If swallowed, do not induce vomiting unless directed to do so by medical personnel. Get medical attention immediately. If there is any discomfort from ingestion, consult a physician.

Inhalation

If inhaled, remove to fresh air. Get medical attention immediately.

5. Fire Fighting Measures

Flash Point: NONE °F
Flash Point Method: NONE
Lower Explosive Limit: N/A
Upper Explosive Limit: N/A

Fire And Explosion Hazards

Material will not burn until all water has evaporated. Cans may burst open and splatter material if temperatures reach 212 deg F and above.

Extinguishing Media

Foam, CO2, Dry chemical, Water fog.

Fire Fighting Instructions

Firefighters should wear self-contained breathing apparatus and full protective gear.

6. Accidental Release Measures

Clean up spill immediately. Cover with absorbent to contain. Collect and dispose. Use appropriate containers to avoid environmental contamination. Avoid runoff to waterways and sewers. Avoid release to the environment. Use appropriate personal protective equipment (PPE).

7. Handling And Storage

Handling And Storage Precautions

Store in cool, dry areas away from sunlight, heat and heat sources. Protect from freezing.

Work/Hygienic Practices

Wash thoroughly with soap and water after handling. Use good personal hygiene. Observe good housekeeping practices.

AcrylPro Ceramic Tile Mastic

8. Exposure Controls/Personal Protection

Eye/Face Protection

Safety glasses with side shields or goggles recommended.

Skin Protection

Chemical-resistant gloves.

Respiratory Protection

General room ventilation is normally adequate. In case of inadequate ventilation, use NIOSH-approved respirator.

Other/General Protection

General ventilation is usually sufficient. Fan or other device maybe needed if used in small and enclosed areas.

Ingredient(s) - Exposure Limits

Calcium Carbonate

OSHA - PEL - TWA - 15mg/m3

Niosh - REL 10 mg/m3 ACGIH- TLV - 10 mg/m3

OSHA DEL TIMA 5 mg/

OSHA - PEL - TWA - 5 mg/m3 Adequate clothing to prevent skin contact.

9. Physical And Chemical Properties

Appearance

White paste

Odor

Mild acrylic odor.

Chemical Type: Mixture Physical State: Liquid Boiling Point: 212 °F Specific Gravity: 1.6

Vapor Density: HEAVIER THAN AIR

Solubility: Dilutable in water

Evaporation Rate: Slower than ether

10. Stability And Reactivity

Stability: Stable

Hazardous Polymerization: Will not occur

Incompatible Materials

Avoid contact with strong oxidizers.

Hazardous Decomposition Products

Thermal decomposition in air may result in carbon monoxide and / or carbon dioxide.

Conditions To Avoid (Polymerization)

Hazardous polymerization will not occur. Heat may cause pressure build-up in closed containers

11. Toxicological Information

Chronic/Carcinogenicity

Contains chemicals that are on California Prop 65 list.

Reproductive Effects

May contain trace amounts of chemicals that caused birth defects in animal studies. It did not cause harm to the animal or fetus when applied on skin.

AcrylPro Ceramic Tile Mastic

11. Toxicological Information - Continued

Ingredient(s) - Toxicological Data

Acrylic Copolymer
Oral >5000mg / kg - rat

12. Ecological Information

No Data Available...

13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations and industry standards.

RCRA Information

Not considered RCRA waste

14. Transport Information

DOT Shipping Label

Not Regulated

15. Regulatory Information

Ingredient(s) - State Regulations

Acrylic Copolymer

California - Proposition 65

Calcium Carbonate

New Jersey - Workplace Hazard Pennsylvania - Workplace Hazard Massachusetts - Hazardous Substance

Canadian Regulatory Information

Not a WHMIS controlled material.

16. Other Information

HMIS Rating

Health: 1 Fire: 0 Reactivity: 0

Personal Protection: B

Revision/Preparer Information

MSDS Preparer: Mike Green

MSDS Preparer Phone Number: (562) 968-2980 ext 115 This MSDS Supersedes A Previous MSDS Dated: 04/24/2006

Disclaimer

THE INFORMATION PRESENTED HERE IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE, WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED, THAT THE INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.

CUSTOM BUILDING PRODUCTS

Printed Using MSDS Generator™ 2000