Material Safety Data Sheet

0646 Masonry & Concrete Repair – Acrylic – Gray – All labels except ACE

MSDS No. 0050 Rev. 7

Emergency Phone No. (918)825-5744

	SECTION 1 – P	RODUCT NAME &	MANUFACTURER 1	INFORM	ATION			
PRODUCT NAME	AME Masonry & Concrete Repair Caulk – Acrylic Latex - Gray							
MANUFACTURER'S N TELEPHONE NUMBER								
STREET ADDRESS	4175 Webb Street							
CITY / STATE / ZIP	Pryor, Oklahoma 7	4361						
SECTIO	ON 2 – COMPOSITI	ON / HAZARDOUS	INGREDIENTS	%	TLV	PEL	UNITS	
PRODUCT CONSISTS	OF:							
Calcium Carbo	onate ** (1317-65-3)			<60	10	15	mg/m3	
Acrylic Emuls	ion (mixture)			<30	NE	NE		
Benzoate Este	r (proprietary)			<6	NE	NE		
Petroleum Dis	tillate (64742-48-9)			<1	100	100	ppm	
Non hozordou	a in anadianta*			<25	NA	NA		
Non-hazardous ingredients*				<23	INA	NA		
*Unlisted ingredients are not considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200). Calculated VOC: < 1.5%/wt, < 25 g/L. CARB Compliance: Yes. Prop 65 Ingredients: Yes (See Section 16)								
	-							
	S	ECTION 3 – HAZAR	DS IDENTIFICATION	ON				
PRIMARY ROUTE(S) OF ENTRY	Skin Contact	Skin Absorption		⊠ Inhalat	tion	⊠ Inge	estion	
EMERGENCY OVERVIEW	Textured gray paste w/ slight odor. Harmful if swallowed. May cause eye, nose, skin, respiratory tract & throat irritation.							
EFFECTS OF OVEREXPOSURE	May cause eye, skin, nose, throat & respiratory tract irritation.							
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE	None known.							
		SECTION 4 – FIRS	T AID MEASURES					
SKIN CONTACT								
EYE CONTACT	Immediately flush w/ large quantities of water for @ least 15 minutes until irritation subsides. Get medical attention.							
INHALATION	Remove to fresh air. If breathing difficult, leave area to obtain fresh air. If breathing remains difficult, get medical attention.							
INGESTION	DO NOT INDUCE VOMITING. Never give anything by mouth to an unconscious person. Get immediate medical attention.							
							<u></u>	

SECTION 5 – FIRE FIGHTING MEASURES							
FLAMMABLE Yes No							
EXTINGUISHING Carbon Dioxide, Dry Chemical, Foam MEDIA							
FLASHPOINT (°F) & >200F (Seta Closed Cup) METHOD	UPPER EXPLOSIVE LIMIT NE (% BY VOLUME)						
LOWER EXPLOSIVE LIMIT NE (% BY VOLUME)	AUTOIGNITION NE TEMPERTURE (°F)						
UNUSUAL FIRE & EXPLOSION HAZARDS None known.							
SPECIAL Wear self-contained breathing apparatus pressure demand (NIOSH approved or equivalent) & full protective gear. Use water spray to FIREFIGHTING cool exposed surfaces. PROCEDURES							
SECTION 6 - ACCIDENT	'AL RELEASE MEASURES						
PROCEDURES Wear proper protective equipment (Section 8). Use absorbent material or scrape up dried material & place in approved container.							
SECTION 7 – HAN	DLING & STORAGE						
HANDLING PROCEDURES & EQUIPMENT Keep out of reach of children & pets. Do not take internally. Do not breathe vapors. Use only w/ adequate ventilation. Wash thoroughly after handling. Avoid contact w/ eyes, skin & clothing. Open windows & doors to ensure cross-ventilation & fresh air during application & curing.							
STORAGE REQUIREMENTS Close container after each use. Store containers away from caustics & oxidizers.	om excessive heat & freezing. Do not store @ temperatures above 120F. Store						
SECTION 8 – EXPOSURE CONTROL / PERSONAL PROTECTION							
RESPIRATORY In case of insufficient ventilation, wear suitable respiratory equipment. A NIOSH-approved air purifying respirator w/ organic vapor cartridge may be necessary under circumstances where concentrations are expected to exceed exposure limits.							
EYEWEAR Goggles or safety glasses w/ side shields.							
CLOTHING / GLOVES Rubber gloves (Neoprene recommended). Other protective equipments	ent not required under normal use.						
HYGENIC PRACTICES Remove & wash contaminated clothing before re-use. Wash hands before breaks & @ end of workday.							
SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES							
	DOOR & Mild acrylic odor. Textured gray paste. PPEARANCE						
	APOR DENSITY Heavier than air AIR=1)						
EVAPORATION RATE NE B	OILING RANGE (°F) NE						
1 ipproximately / to 10	OLUBILITY IN Appreciable, before cure. VATER						
	6/WT VOLATILE < 20 INV)						
SECTION 10 - STABILITY AND REACTIVITY							
STABILITY Yes No Stable under normal conditions.							
INCOMPATABILITY Yes No Incompatible w/ strong bases & oxidizers.							
CONDITIONS TO AVOID Excessive heat & freezing.							
HAZARDOUS POLYMERIZATION/HAZARDOUS DECOMPOSITION PRODUCTS Hazardous polymerization will not occur under normal conditions. Normal decomposition products, ie: COx, NOx.							

SECTION 11 - TOXICOLOGICAL INFORMATION / CARCINOGENICITY				
ACGIH	Small amount of Silica, crystalline present in Calcium Carbonate & trace residual Formaldehyde present in base emulsion are suspected human carcinogens.			
OSHA	Trace residual Formaldehyde present in base emulsion viewed as a possible cancer hazard.			
IARC	Trace residual Formaldehyde: Human carcinogen.			
NTP	Silica, crystalline, present in small amount in Calcium Carbonate Filler: Known carcinogen. Trace residual Formaldehyde: Anticipated carcinogen.			
DATA WITH POSSIBLE RELEVANCE TO HUMANS	1 found contains trace amounts of residual Formalucity activity Formalucity as a potential calcinoscii. IANC lucitities			

SECTION 12 - ECOLOGICAL INFORMATION

AQUATIC TOXICITY

Not known or expected under normal use.

SECTION 13 – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

Dispose of material in accordance w/ Federal, State & Local regulations.

EPA WASTE CODE IF

None.

SECTION 14 – TRANSPORT INFORMATION

SPECIAL SHIPPING

Shipping information applicable for domestic ground transport only. Different categorization may be necessary if shipped via other modes of transportation &/or to non-domestic destinations. PRODUCT NOT REGULATED BY DOT.

SECTION 15 – REGULATORY INFORMATION						
CERCLA – SARA HAZARD CATEGORY	Immediate health hazard; chronic health hazard.	U.S. STATE REGS	See Section 16.			
SARA 313	None.	TSCA	All ingredients either on TSCA Inventory or exempt. Product contains no TSCA 12(B) materials, if exported from the U.S.			

SECTION 16 – OTHER INFORMATION / SPECIAL PRECAUTIONS / LEGEND

NJ Right-to-Know: (Top 5 Ingredients): Calcium Carbonate (1317-65-3), Base Acrylic Emulsion Blend (mixture), Benzoate Ester (proprietary), Propylene Glycol (57-55-6), Petroleum Distillate (64742-48-9). Pennsylvania Right-to-Know (Non-Haz @ >3%): Water (7732-18-5). Ingredients Known to State of California to cause cancer &/or developmental toxicity &/or reproductive toxicity: Formaldehyde (50-00-0), Silica, Crystalline (14808-60-7). HMIS Ratings: Health: 1, Flammability: 1, Reactivity: 0, Personal Protection: X. Color dispersion may contain carbon black. WARNING: Product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

<u>LEGEND</u>: NA – Not Applicable, NE – Not Established, UN – Unavailable, VOC – Volatile Organic Compound, PEL – Permissible Exposure Limit, TLV – Threshold Limit Value, STEL – Short Term Exposure Limit, MSDS – Material Safety Data Sheet, ACGIH – American Conference of Governmental Industrial Hygienists, SARA – Superfund Amendments & Reauthorization Act of 1986, OSHA – Occupational Safety & Health Administration, HMIS – Hazardous Materials Identification System, NTP – National Toxicology Program, CEIL – Ceiling Exposure Limit, CASRN (CAS Number) – Chemical Abstracts Service Registry Number, TSCA – Toxic Substances Control Act

Reviewed By: Larry G. Brandon VP Technology & General Manager February 4, 2010

NAME TITLE

The information contained herein has been developed based upon currently available scientific data. New information may be developed from time to time which may render the conclusions of this report obsolete. Therefore, no warranty is extended as to the applicability of this information to the user's intended purpose or for the consequences of its use or misuse.