MATERIAL SAFETY DATA SHEET

GARDNER-GIBSON CORPORATION STRIET ADDRESS 4161 E. THA AVENUE TAMPA, FL 33605 EMERGENCY TELEPHONE NUMBER 1-800-424-9300 PRODUCT CLASS MANUFACTURER'S CODE IDENTIFICATION ACTYLIC COATING *BJ-5527 TRADE NAME Black Jack White Elastomeric Roof Coating SECTION II - COMPOSITION/ INGREDIENTS INGREDIENT By Weight Black Jack White Elastomeric Roof Coating SECTION III - COMPOSITION/ INGREDIENTS INGREDIENT By Weight Black Jack White Elastomeric Roof Coating SECTION III - PHYSICAL DATA BEIDILING RANGE: 212°F - 215°F VAPOR PRESSURE: 25 mm Hg & 68°F VAPOR PRESSURE: 25	Date Issued: 12/21/07				Page 1 of 2
GARDNER-GIBSON CORPORATION STREET ADDRESS 4161 E. 7TH AVENUE TAMPA, FL 33605 EMERGENCY TELEPHONE NUMBER 1-800-424-9300 PRODUCT CLASS Acrylic Coating # BJ-5527 TRADE NAME Black Jack White Elastomeric Roof Coating SECTION II - COMPOSITION/ INGREDIENTS INGREDIENT BY Weight BY WEIGH BY BY BY WEIGH BY BY BY WEIGH BY BY BY WEIGH BY B	SECTION I – CO	MPANY AND	PRODUCT ID	ENTIFICAT	ΓΙΟΝ
EMERGENCY TELEPHONE NUMBER 1-800-424-9300 PRODUCT CLASS Acrylic Coating # BJ-5527 TRADE NAME Black Jack White Elastomeric Roof Coating SECTION II - COMPOSITION/ INGREDIENTS INGREDIENT Bethylene Glycol CAS # 107-21- Acrylic Polymer CAS # Not available - mixture N.E Not Established SECTION III - PHYSICAL DATA BOILING RANGE: 212°F - 215°F VAPOR PRESSURE: 25 mm Hg @ 68°F VAPOR STATE Paste SECTION IV - FIRE AND EXPLOSION HAZARD DATA FIASH POINT: WATER BASED - Not Applicable EEL - Not Applicable EEL - Not Applicable EETING CUISHING MEDIA - Carbon dioxide, dry chemical, foam, or water spray UNUSUAL FIRE AND EXPLOSION HAZARD be worn in fighting large fires involving chemicals SECTION V - REACTIVITY DATA STABILITY: UNSTABLE STABLE CONDITIONS TO AVOID: Store away from strong oxidizing materials. PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in a cool, dry place. Keep container closed when not in use. Protect from freezing.	MANUFACTURER'S NAME GARDNER-GIBSON CORPORATION	 ON			
# BJ-5527 **TRADE NAME Black Jack White Elastomeric Roof Coating **SECTION II - COMPOSITION/ INGREDIENTS **INGREDIENT** PERCENT TLV PEL - TWA	STREET ADDRESS 4161 F 7TH AVENUE			IP CODE	
TRADE NAME SECTION II - COMPOSITION INGREDIENT ItV PEL - TWA By Weight ItV PEL - TWA ItV PEL - TWA By Weight ItV PEL - TWA ItV PEL - TWA By Weight ItV PEL - TWA ItV PEL - TWA By Weight ItV PEL - TWA			IFA, FL 55005		
#BJ-5527 MANUFACTURERS CODE IDENTIFICATION #BJ-5527 SECTION II - COMPOSITION / INGREDIENTS		<u>SER</u>			
TRADE NAME Black Jack White Elastomeric Roof Coating SECTION II - COMPOSITION/ INGREDIENTS		MAN	UFACTURER'S CO	DE IDENTIFIC <i>i</i>	ATION
SECTION II - COMPOSITION/ INGREDIENTS INGREDIENT PERCENT By Weight PEL - TWA By Weight Dispersible PERCENT Dispersible PHYSICAL DATA SECTION III - PHYSICAL DATA BOILING RANGE: 212°F - 215°F VAPOR DENSITY HEAVIER LIGHTER, THAN AIR VAPOR PRESSURE: 25 mm Hg @ 68°F EVAPORATION RATE FASTER SIGNER, THAN PERCENT VOLUME: 50 % 11.5 lbs. SOLUBILITY IN WATER: Dispersible PHYSICAL STATE: Paste PH 8.5 SECTION IV - FIRE AND EXPLOSION HAZARD DATA FLASH POINT: WATER BASED - Not Applicable Explosion Hazard: Not Applicable EXTINGUISHING MEDIA - Carbon dioxide, dry chemical, foam, or water spray UNUSUAL FIRE AND EXPLOSION HAZARDS - None SPECIAL FIRE FIGHTING PROCEDURES - Water can be used to cool fire-exposed containers. Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals SECTION V - REACTIVITY DATA STABILITY: UNSTABLE STABLE CONDITIONS TO AVOID: Store away from strong oxidizing materials. PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in a cool, dry place. Keep container closes when not in use. Protect from freezing.	Acrylic Coating	# BJ	J-5527		<u> </u>
PERCENT By Weight By Wei	TRADE NAME Black Jack White Elastomeric Roof Coa	ating			
By Weight 1.0 50 ppm 50	SECTION	III - COMPOSI	TION/ INGRI	EDIENTS	
By Weight 1.0 50 ppm 50	INGREDIENT		PERCENT	TLV	PEL - TWA
Acrylic Polymer CAS # Not available - mixture N.E. – Not Established SECTION III — PHYSICAL DATA BOILING RANGE: 212°F - 215°F VAPOR PRESSURE: 25 mm Hg @ 68°F EVAPORATION RATE ☐ FASTER EVAPORATION RATE ☐ FASTER SOLUBILITY IN WATER: Dispersible SECTION IV — FIRE AND EXPLOSION HAZARD DATA FLASH POINT: WATER BASED — Not Applicable LEL — Not Explosion Hazard: Not Applicable LEL — Not Applicable SECTION IV — FIRE AND EXPLOSION HAZARD DATA FLASH POINT: WATER BASED — Not Applicable LEL — Not Applicable SECTION IV — FIRE AND EXPLOSION HAZARDS — None SPECIAL FIRE FIGHTING PROCEDURES - Water can be used to cool fire-exposed containers. Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals SECTION V - REACTIVITY DATA STABILITY: ☐ UNSTABLE ☐ STABLE CONDITIONS TO AVOID: Store away from strong oxidizing materials. PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in a cool, dry place. Keep container closed when not in use. Protect from freezing.			By Weight	50	50 =
SECTION III — PHYSICAL DATA BOILING RANGE: 212°F - 215°F	CAS # 107-21-1		1.0	50 ppm	50 ppm
SECTION III – PHYSICAL DATA BOILING RANGE: 212°F - 215°F	Acrylic Polymer		< 40.0	N.E.	N.E.
SECTION IV – FIRE AND EXPLOSION HAZARD DATA FLASH POINT: WATER BASED – Not Applicable LEL – Not Applicable EXTINGUISHING MEDIA - Carbon dioxide, dry chemical, foam, or water spray UNUSUAL FIRE AND EXPLOSION HAZARDS – None SPECIAL FIRE FIGHTING PROCEDURES - Water can be used to cool fire-exposed containers. Self- contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals SECTION V - REACTIVITY DATA STABILITY: UNSTABLE STABLE CONDITIONS TO AVOID: Store away from strong oxidizing materials. PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in a cool, dry place. Keep container closed when not in use. Protect from freezing.	BOILING RANGE: 212°F - 215°F VAPOR PRESSURE: 25 mm Hg @ 68°F EVAPORATION RATE	VAPOR DENSITY DWER, THAN PERCI	⊠ HEAVIER	LIGHTER WEIGHT	PER GALLON:
FLASH POINT: WATER BASED – Not Applicable LEL – Not Applicable EXTINGUISHING MEDIA - Carbon dioxide, dry chemical, foam, or water spray UNUSUAL FIRE AND EXPLOSION HAZARDS – None SPECIAL FIRE FIGHTING PROCEDURES - Water can be used to cool fire-exposed containers. Self- contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals SECTION V - REACTIVITY DATA STABILITY: UNSTABLE STABLE CONDITIONS TO AVOID: Store away from strong oxidizing materials. PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in a cool, dry place. Keep container closed when not in use. Protect from freezing.	SOLUBILITY IN WATER: Dispersible		-	11 . 5 Lb	
EXTINGUISHING MEDIA - Carbon dioxide, dry chemical, foam, or water spray UNUSUAL FIRE AND EXPLOSION HAZARDS − None SPECIAL FIRE FIGHTING PROCEDURES - Water can be used to cool fire-exposed containers. Self- contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals SECTION V - REACTIVITY DATA STABILITY: □ UNSTABLE □ STABLE □ CONDITIONS TO AVOID: Store away from strong oxidizing materials. PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in a cool, dry place. Keep container closed when not in use. Protect from freezing.	SECTION IV -	- FIRE AND EX	KPLOSION HA	AZARD DA	ГА
SECTION V - REACTIVITY DATA STABILITY: UNSTABLE STABLE CONDITIONS TO AVOID: Store away from strong oxidizing materials. PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in a cool, dry place. Keep container closed when not in use. Protect from freezing.	LEL – Not Applicable EXTINGUISHING MEDIA - Carbon did	oxide, dry chemic	-		icable
STABILITY: UNSTABLE STABLE CONDITIONS TO AVOID: Store away from strong oxidizing materials. PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in a cool, dry place. Keep container closed when not in use. Protect from freezing.					
oxidizing materials. PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in a cool, dry place. Keep container closed when not in use. Protect from freezing.	SE	CTION V - REA	CTIVITY DA	ТА	
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in a cool, dry place. Keep container closed when not in use. Protect from freezing.	STABILITY: UNSTABLE ST	ABLE			tore away from strong
	when not in use. Protect from freezing.		GE: Store in a co	ol, dry place.	-
HAZARDOUS POLYMERIZATION: ☐ MAY OCCUR ☐ WILL NOT OCCUR	HAZARDOUS POLYMERIZATION: MA	AY OCCUR	⊠ WILL NO	Г OCCUR	

SECTION VI - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE -

ACUTE EFFECTS:

EYES: Direct contact may cause slight to moderate irritation. SKIN: Mild irritation may occur in some

individuals.

INHALATION: Irritates respiratory passages slightly, may cause dizziness. INGESTION: May cause nausea.

PROLONGED/REPEATED EXPOSURE EFFECTS:

SKIN: Minor skin irritation may occur. INHALATION: May cause irritation to respiratory tract.

INGESTION: May cause nausea.

EMERGENCY FIRST AID PROCEDURES –

EYES: Flush with water for 15 minutes. Get medical attention if irritation persists.

SKIN: Wash with soap and water or waterless cleanser. Get medical attention if irritation develops or

INHALATION: If symptoms develop, move to fresh air.

INGESTION: Do not induce vomiting. If symptoms develop, seek medical advice from a physician.

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

SECTION VII – SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Observe all personal protection equipment recommendations described in Section VIII. Wipe up or scrape up and contain for disposal. Final cleaning may require use of hot water and/or detergents. Dispose of saturated absorbent or cleaning materials appropriately.

WASTE DISPOSAL METHOD: Dispose of unused material in accordance with Federal, State, and Local Regulations.

SECTION VIII – PERSONAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Use with adequate ventilation.

SKIN PROTECTION: Chemical resistant gloves are recommended for prolonged exposure.

EYE PROTECTION: Safety glasses with side shields. OTHER PROTECTIVE EQUIPMENT: None required.

SECTION IX – TRANSPORTATION and REGULATORY INFORMATION

DOT Proper Shipping Name: Not Regulated by D.O.T. **DOT UN/NA Number:** None **DOT UN/NA Number:** None **DOT Example 1 DOT Hazard Class:** None **Packing Group:** None

SARA Title III: No substances are contained in this product subject to the reporting requirements of EPCRA Section 313 of the Superfund Amendments and Reauthorization Act, 40 CFR Part 372.

TSCA Status: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

California Proposition 65: This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm.

SECTION X – OTHER INFORMATION

OTHER PRECAUTIONS: KEEP OUT OF THE REACH OF CHILDREN. KEEP CONTAINER CLOSED WHEN NOT IN USE. PROTECT FROM FREEZING.

Hazardous Materials Identification System (HMIS)

	Personal Protection	Reactivity	Flammability	Health
	В	0	0	1
Prepared by: Morton				

Jones