

**GE5050
Silicone Rubber Sealant****1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

Manufactured By: Waterford Plant
260 Hudson River Rd
Waterford NY 12188

Revised: 09/15/2009
Preparer: PRODUCT STEWARDSHIP COMPLIANCE AND STANDARDS
CHEMTREC 1-800-424-9300

Chemical Family/Use: Silicone Rubber
Formula: Mixture

HMIS

Flammability: 0 Reactivity: 0 Health: 1

NFPA

Flammability: 1 Reactivity: 0 Health: 1

2. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW**

WARNING! May be harmful if swallowed, inhaled or absorbed through skin. Irritating to eyes, respiratory system and skin. May cause central nervous system depression. May cause adverse reproductive effects. Adverse reproductive effects reported in animals.

Form: paste**Color:** metallic**Odor:** Ammonia**POTENTIAL HEALTH EFFECTS****INGESTION**

May be harmful if swallowed. May cause central nervous system effects. May cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

SKIN

Uncured product contact will irritate lips, gums and tongue. May cause skin irritation. May be absorbed through skin and produce effects as listed under "Ingestion".

INHALATION

Applies in uncured state. May cause respiratory tract irritation. May also cause other effects as listed under "Ingestion".

EYES

Eye irritation on contact with the uncured product.

MEDICAL CONDITIONS AGGRAVATED

Respiratory disorder Central nervous system disorders. Skin disorders.

**GE5050
Silicone Rubber Sealant****SUBCHRONIC (TARGET ORGAN)**

Liver; Central nervous system

CHRONIC EFFECTS / CARCINOGENICITY

This product or one of its ingredients present at 0.1% or more is NOT listed as a carcinogen or suspected carcinogen by NTP, IARC, or OSHA.

ROUTES OF EXPOSURE

Dermal; Eyes

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>PRODUCT COMPOSITION</u>	<u>CAS REG NO.</u>	<u>WGT. %</u>
<u>A. HAZARDOUS</u>		
Hexamethyldisilazane	999-97-3	1 - 5 %
Methyltrimethoxysilane	1185-55-3	1 - 5 %
DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE	64742-46-7	5 - 10 %
<u>B. NON-HAZARDOUS</u>		
Methoxypolydimethylsiloxane	68037-58-1	60 - 100 %
Polydimethylsiloxane	63148-62-9	10 - 30 %
Treated Filler	68611-44-9	10 - 30 %

4. FIRST AID MEASURES**INGESTION**

Do not induce vomiting. If victim is conscious, give 1-3 glasses of water to drink. Never give anything by mouth to an unconscious person. Get medical attention if irritation persists.

SKIN

To clean from skin, remove completely with a dry cloth or paper towel, before washing with detergent and water. If skin irritation persists, call a physician.

INHALATION

If inhaled, remove to fresh air. If not breathing give artificial respiration using a barrier device. If breathing is difficult give oxygen. Get medical attention.

**GE5050
Silicone Rubber Sealant****EYES**

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

NOTE TO PHYSICIAN

None known.

5. FIRE-FIGHTING MEASURES

FLASH POINT: > 93.3 °C; 200 °F
METHOD: estimated
IGNITION TEMPERATURE: Unknown
FLAMMABLE LIMITS IN AIR - LOWER (%): not applicable
FLAMMABLE LIMITS IN AIR - UPPER (%): N

SENSITIVITY TO MECHANICAL IMPACT: No

SENSITIVITY TO STATIC DISCHARGE

Sensitivity to static discharge is not expected.

EXTINGUISHING MEDIA

All standard extinguishing agents are suitable.

SPECIAL FIRE FIGHTING PROCEDURES

Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES**ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED**

Wipe, scrape or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section.

7. HANDLING AND STORAGE**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE**

Avoid contact with skin and eyes. Keep container tightly closed. Remove contact lenses before using sealant. Do not handle lenses until all sealant has been cleaned from the fingertips, nails and cuticles. Residual sealant may remain on fingers for several days and transfer to lenses and cause severe eye irritation. Product releases methanol during application and curing. Product releases ammonia during application and curing.

**GE5050
Silicone Rubber Sealant****STORAGE**

Store away from heat, sources of ignition, and incompatibles. Keep out of the reach of children.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**ENGINEERING CONTROLS**

Eyewash stations; Showers; Ventilation and other forms of engineering controls are preferred for controlling exposures. Respiratory protection may be needed for non-routine or emergency situations.

RESPIRATORY PROTECTION

If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134).

PROTECTIVE GLOVES

Cloth gloves.

EYE AND FACE PROTECTION

Safety glasses

OTHER PROTECTIVE EQUIPMENT

Wear suitable protective clothing and eye/face protection.

Exposure Guidelines

Component	CAS RN	Source	Value
------------------	---------------	---------------	--------------

Absence of values indicates none found

PEL - OSHA Permissible Exposure Limit; TLV - ACGIH Threshold Limit Value; TWA - Time Weighted Average; INTL REL - Internal Recommended Exposure Limit

OSHA revoked the Final Rule Limits of January 19, 1989 in response to the 11th Circuit Court of Appeals decision (AFL-CIO v. OSHA) effective June 30, 1993. See 29 CFR 1910.1000 (58 FR 35338).

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT - C & F:	not applicable
VAPOR PRESSURE (20 C) (MM HG):	not applicable
FREEZING POINT:	not applicable
PHYSICAL STATE:	paste
ODOR:	Ammonia
COLOR:	metallic
EVAPORATION RATE (BUTYL ACETATE=1):	< 1
SPECIFIC GRAVITY (WATER=1):	ca. 1.05
DENSITY:	ca. 1.05 g/cm ³

**GE5050
Silicone Rubber Sealant**

ACID / ALKALINITY (MEQ/G):	Unknown
pH:	not applicable
SOLUBILITY IN WATER (20 C):	negligible
SOLUBILITY IN ORGANIC SOLVENT (STATE SOLVENT):	Toluene
VOLATILE ORGANIC CONTENT:	2.2 %(m)
VOC EXCL. H2O & EXEMPTS (G/L):	27 g/l

10. STABILITY AND REACTIVITY**STABILITY**

Stable

HAZARDOUS POLYMERIZATION

Will not occur.

HAZARDOUS THERMAL DECOMPOSITION / COMBUSTION PRODUCTS

Carbon monoxide; Carbon dioxide (CO₂); Silicon dioxide.; Methanol; formaldehyde; Ammonia; This product contains methylpolysiloxanes which can generate formaldehyde at approximately 300 degrees Fahrenheit (150°C) and above, in atmospheres which contain oxygen. Formaldehyde is a skin and respiratory sensitizer, eye and throat irritant, acute toxicant, and potential cancer hazard. A MSDS for formaldehyde is available from Momentive.

INCOMPATIBILITY (MATERIALS TO AVOID)

None known.

CONDITIONS TO AVOID

Applies in uncured state. Vapor and/or liquid react with water to form ammonia.

11. TOXICOLOGICAL INFORMATION**ACUTE ORAL**

Remarks: Unknown

ACUTE DERMAL

Remarks: Unknown

ACUTE INHALATION

Remarks: Unknown

OTHER

Contains dibutyltin compound(s) - May impair fertility. May cause harm to unborn child.

SENSITIZATION

no data available

**GE5050
Silicone Rubber Sealant**

SKIN IRRITATION

no data available

EYE IRRITATION

no data available

MUTAGENICITY

Unknown

OTHER EFFECTS OF OVEREXPOSURE

Methanol released during curing.

12. ECOLOGICAL INFORMATION**ECOTOXICITY**

no data available

DISTRIBUTION

no data available

CHEMICAL FATE

no data available

13. DISPOSAL CONSIDERATIONS**DISPOSAL METHOD**

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION**Further Information:**

This product is not regarded as dangerous goods according to the national and international regulations on the transport of dangerous goods.

15. REGULATORY INFORMATION**Inventories**TSCA list y (positive listing)
Philippines Inventory of Chemicals y (positive listing)
and Chemical Substances
(PICCS)

**GE5050
Silicone Rubber Sealant**

Canada NDSL Inventory	n (Negative listing)
EU list of existing chemical substances	y (positive listing)
Australia Inventory of Chemical Substances (AICS)	y (positive listing)
Canada DSL Inventory	y (positive listing)
Korea Existing Chemicals Inventory (KECI)	y (positive listing)
China Inventory of Existing Chemical Substances	y (positive listing)

For inventories that are marked as quantity restricted or special cases, please contact Momentive.

US Regulatory Information**SARA (311,312) HAZARD CLASS**

Acute Health Hazard

SARA (313) CHEMICALS**CALIFORNIA PROPOSITION 65**

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

Canadian Regulatory Information**WHMIS HAZARD CLASS**

D2A - Very Toxic Material Causing Other Toxic Effects

D2B - Toxic Material Causing Other Toxic Effects

16. OTHER INFORMATION**OTHER**

C = ceiling limit NEGL = negligible EST = estimated NF = none found NA = not applicable
UNKN = unknown NE = none established REC = recommended ND = none determined V = recommended by vendor
SKN = skin TS = trade secret R = recommended MST = mist
NT = not tested STEL = short term exposure limit ppm = parts per million ppb = parts per billion
By-product= reaction by-product, TSCA inventory status not required under 40 CFR part 720.30(h-2)., These data are offered in good faith as typical values and not as product specifications.
No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.