

Eagle One™ WET TIRE SHINE / DRESSING
640848

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Ashland	Regulatory Information Number	1-800-325-3751
P.O. Box 2219	Telephone	614-790-3333
Columbus, OH 43216	Emergency telephone number	1-800-ASHLAND (1-800-274-5263)
Product name	Eagle One™ WET TIRE SHINE / DRESSING	
Product code	640848	
Product Use Description	No data	

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid

CAUTION! COMBUSTIBLE LIQUID AND VAPOR. MAY AFFECT THE CENTRAL NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. PROLONGED OR REPEATED CONTACT MAY DRY THE SKIN AND CAUSE IRRITATION AND BURNS.

Potential Health Effects

Exposure routes

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye contact

May cause mild eye irritation. Symptoms include stinging, tearing, and redness.

Skin contact

May cause mild skin irritation. Symptoms may include redness and burning of skin. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, skin burns, and other skin damage.

Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

Eagle One™ WET TIRE SHINE / DRESSING
640848

Inhalation

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: Skin

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness)

Target Organs

Exposure to this material (or a component) has been found to cause kidney damage in male rats. The mechanism by which this toxicity occurs is specific to the male rat and the kidney effects are not expected to occur in humans.

Carcinogenicity

This product (or a component) is a petroleum-derived material. Similar materials and certain compounds occurring naturally in petroleum oils have been shown to cause skin cancer in laboratory animals following repeated exposure without washing or removal. This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA).

Reproductive hazard

There are no data available for assessing risk to the fetus from maternal exposure to this material.

Other information

When heated to temperatures above 150 degrees C in the presence of air, this product can form formaldehyde vapors. Formaldehyde has been identified as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP) and the Occupational Safety and Health Administration (OSHA). Formaldehyde is irritating to the eyes, nose, throat, and airways, and can cause an allergic reaction (causes narrowing of the air passages of the lungs, sweating, flushing, hives, rapid heart rate, and lowered blood pressure). In addition, formaldehyde can cause an allergic skin reaction (delayed skin rash which may be followed by blistering, scaling and other skin effects). It is harmful if inhaled, swallowed or absorbed through skin.

Eagle One™ WET TIRE SHINE / DRESSING
640848

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components	CAS-No.	Concentration
SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC	64742-96-7	>=80-<90%
DIMETHYL SILICONES AND SILOXANES	63148-62-9	>=10-<15%
MODIFIED SILICONE COPOLYMER		>=1.5-<5%

4. FIRST AID MEASURES

Eyes

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to physician

Hazards: No information available.

Treatment: No information available.

Eagle One™ WET TIRE SHINE / DRESSING
640848

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Dry chemical, Carbon dioxide (CO₂), Water spray

Hazardous combustion products

Aldehydes, carbon dioxide and carbon monoxide, Hydrocarbons, formaldehyde, Hydrogen, silicon oxides

Precautions for fire-fighting

If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning material with water used for cooling purposes.

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIA

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Ensure adequate ventilation. Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Pay attention to the spreading of gases especially at ground level (heavier than air) and to the direction of the wind.

Environmental precautions

Prevent spreading over a wide area (e.g. by containment or oil barriers). Do not let product enter drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.

Methods for cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Other information

Eagle One™ WET TIRE SHINE / DRESSING
640848

Comply with all applicable federal, state, and local regulations. Suppress (knock down) gases/vapours/mists with a water spray jet.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.

Storage

Store in a cool, dry, ventilated area, away from incompatible substances. Store in a cool, dry, ventilated area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure controls

General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Eye protection

Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection

Eagle One™ WET TIRE SHINE / DRESSING
640848

Wear resistant gloves (consult your safety equipment supplier).
Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

Respiratory protection

Respiratory protection is not required under normal conditions of use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Form	no data available
Colour	no data available
Odour	no data available
Boiling point/boiling range	347 °F / 175 °C Calculated Phase Transition Liquid/Gas
Melting point/range	no data available
Sublimation point	no data available
pH	no data available
Flash point	176 °F / 80 °C Calculated Flash Point
Ignition temperature	no data available
Evaporation rate	no data available
Lower explosion limit/Upper explosion limit	0.7 %(V) / 6 %(V) Calculated Explosive Limit
Particle size	no data available
Vapour pressure	6.666 hPa @ 68 °F / 20 °C Calculated Vapor Pressure
Relative vapour density	no data available
Density	0.839 g/cm3 @ 68 °F / 20 °C
Bulk density	No data
Water solubility	no data available
Solubility	no data available
Partition coefficient: n-octanol/water	no data available
log Pow	no data available
Autoignition temperature	no data available
Viscosity, dynamic	no data available
Viscosity, kinematic	no data available
Solids in Solution	no data available

Eagle One™ WET TIRE SHINE / DRESSING
640848

Decomposition temperature	no data available
Burning number	no data available
Dust explosion constant	no data available
Minimum ignition energy	no data available

10. STABILITY AND REACTIVITY

Stability

Stable.

Conditions to avoid

Heat, flames and sparks.

Incompatible products

Strong oxidizing agents, strong reducing agents

Hazardous decomposition products

Aldehydes, carbon dioxide and carbon monoxide, Hydrocarbons, formaldehyde, Hydrogen, silicon oxides

Hazardous reactions

Product will not undergo hazardous polymerization.

Thermal decomposition

No data

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity

SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC : LD 50 Rat: > 5 g/kg

DIMETHYL SILICONES AND SILOXANES : LD 50 Rat: > 5 g/kg

MODIFIED SILICONE COPOLYMER : no data available

Acute inhalation toxicity

SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC : LC 50 Rat: > 5 mg/l; 4 h

DIMETHYL SILICONES AND SILOXANES : no data available

Eagle One™ WET TIRE SHINE / DRESSING
640848

MODIFIED SILICONE COPOLYMER : no data available

Acute dermal toxicity

SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC : LD 50
Rat:
> 2,000 mg/kg

DIMETHYL SILICONES AND SILOXANES : LD 50
Rabbit:
> 10,200 mg/kg

MODIFIED SILICONE COPOLYMER : no data available

12. ECOLOGICAL INFORMATION

Biodegradability

SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC : no data available

DIMETHYL SILICONES AND SILOXANES : no data available

MODIFIED SILICONE COPOLYMER : no data available

Bioaccumulation

SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC : no data available

DIMETHYL SILICONES AND SILOXANES : no data available

MODIFIED SILICONE COPOLYMER : no data available

Ecotoxicity effects

Toxicity to fish

SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC : no data available

DIMETHYL SILICONES AND SILOXANES : 96 h LC 50 Channel catfish (*Ictalurus punctatus*): 2.36
- 4.15 mg/l Method: Renewal; Mortality

MODIFIED SILICONE COPOLYMER : no data available

Eagle One™ WET TIRE SHINE / DRESSING
640848

Toxicity to daphnia and other aquatic invertebrates.

SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC : no data available
DIMETHYL SILICONES AND SILOXANES : 48 h LC 50 Water flea (Daphnia magna): 44.50 mg/l
Method: Static Mortality

MODIFIED SILICONE COPOLYMER : no data available

Toxicity to algae

SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC : no data available
DIMETHYL SILICONES AND SILOXANES : no data available

MODIFIED SILICONE COPOLYMER : no data available

Toxicity to bacteria

SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC : no data available
DIMETHYL SILICONES AND SILOXANES : no data available

MODIFIED SILICONE COPOLYMER : no data available

Biochemical Oxygen Demand (BOD)

SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC : no data available
DIMETHYL SILICONES AND SILOXANES : no data available

MODIFIED SILICONE COPOLYMER : no data available

Chemical Oxygen Demand (COD)

SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC : no data available
DIMETHYL SILICONES AND SILOXANES : no data available

MODIFIED SILICONE COPOLYMER : no data available

Additional ecological information

SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC : no data available
DIMETHYL SILICONES AND SILOXANES : no data available

MODIFIED SILICONE COPOLYMER : no data available

Eagle One™ WET TIRE SHINE / DRESSING
640848

13. DISPOSAL CONSIDERATIONS

Waste disposal methods

For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

14. TRANSPORT INFORMATION

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

U.S. DOT - ROAD

Not dangerous goods

U.S. DOT - RAIL

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TRANSPORT CANADA - ROAD

Not dangerous goods

TRANSPORT CANADA - RAIL

Not dangerous goods

TRANSPORT CANADA - INLAND WATERWAYS

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

Eagle One™ WET TIRE SHINE / DRESSING
640848

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

Not dangerous goods

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

15. REGULATORY INFORMATION

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SARA Hazard Classification

Fire Hazard
Acute Health Hazard

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

New Jersey RTK Label Information

SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC	64742-96-7
DIMETHYL SILICONES AND SILOXANES	63148-62-9
MODIFIED SILICONE COPOLYMER	

Pennsylvania RTK Label Information

SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC	64742-96-7
DIMETHYL SILICONES AND SILOXANES	63148-62-9

Notification status

US. Toxic Substances Control Act	y (positive listing)
Canada. Canadian Environmental Protection Act (CEPA).	y (positive listing)
Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133)	

Eagle One™ WET TIRE SHINE / DRESSING
640848

Australia. Industrial Chemical (Notification and Assessment) Act	y (positive listing)
New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand	y (positive listing)
Japan. Kashin-Hou Law List	y (positive listing)
Korea. Toxic Chemical Control Law (TCCL) List	n (Negative listing)
Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act	y (positive listing)
China. Inventory of Existing Chemical Substances	y (positive listing)

	HMIS	NFPA
Health	1	1
Flammability	2	2
Physical hazards	0	
Instability		0
Specific Hazard	--	--

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).